



# ARG314 Aerodynamic Rain Gauge



**The cost-effective choice of EML gauge for the professional Hydro-Met Services**

Applications	Features and Benefits
<ul style="list-style-type: none"><li>• National Met Services</li><li>• Hydrology catchment projects</li><li>• Hydro-Met stations</li><li>• Industrial customers that need accurate data</li><li>• Weather enthusiasts</li><li>• Flood warning systems</li></ul>	<ul style="list-style-type: none"><li>• Optimum Aerodynamic shape from over 10 years of extensive field research</li><li>• Self-emptying instrument</li><li>• 0.1 or 0.2mm resolution</li><li>• WMO Compliant</li><li>• UK manufactured</li></ul>

All EML gauges are rigorously laboratory and field tested. Outdoor field testing is carried out against a WMO compliant pit gauge at multiple sites.



7 Jupiter Court  
Orion Business Park  
North Shields  
NE29 7SE  
United Kingdom



The unique design and aerodynamic shape of the ARG314 Tipping Bucket precipitation sensor increases measurement accuracy by capturing more rainfall than traditionally shaped cylindrical gauges. The ARG314 is precision-engineered to minimise out-splash and reduce rainfall losses caused by evaporation. The depth, diameter, and angle of the funnel have all been extensively tested and researched to give the optimum accuracy in the field.



The rugged UV resistant material means that the ARG314 can be installed in extremely hostile conditions. This gauge is available in either 0.1mm or 0.2mm resolution (per tip) and comes as standard with a single contact closure reed switch. A dual reed switch upgrade and/or siphon version are available on request. Quality is assured because the gauge is manufactured and assembled by EML in the UK. The ARG314 is a robust and versatile instrument and is compatible with all modern data loggers and event recorders.

Technical Specifications	
Resolution	0.1mm or 0.2mm 0.005 inch (0.01 inch due Q3 2019)
WMO Compliant	Yes
Output	Contact Closure (Reed Switch) – Dual reed switch upgrade available
Typical Accuracy	99% up to 120mm/hr
Rainfall Intensity	0-1000 mm/hr (with mathematical correction - contact EML)
Operating Temperature	1°C - 70°C
Funnel Diameter	20.0cm / 7.87 Inch
Funnel Area	314cm <sup>2</sup> / 48.67 sq. Inch
Height	43.5cm to 46.5cm (with feet adjustment)
Weight	2Kg
Colour	White

Ordering Information	
Order Code	Product
P-780-300	ARG314/STD (0.1mm) - Standard
P-780-301	ARG314/EC (0.1mm) - Standard with 6m cable
P-780-302	ARG314/L (0.1mm) - Standard with plug for internal EML logger
P-780-303	ARG314/STD (0.2mm) - Standard
P-780-304	ARG314/EC (0.2mm) - Standard with 6m cable
P-780-305	ARG314/L (0.2mm) - Standard with plug for internal EML logger
contact sales	ARG314 (0.1 or 0.2mm) with other cable length available on request

Ordering Information - Accessories	
Order Code	Product
P-780-320	ARG314 Dual reed switch upgrade
P-780-319	ARG314 spares kit
contact sales	ARG314 siphon upgrade



7 Jupiter Court  
Orion Business Park  
North Shields  
NE29 7SE  
United Kingdom

Copyright Environmental Measurements Limited (EML)

Distribué en France par Alliance Technologies